213.1636RV

PLUG
16A 3P+E 6h 380-415V 60Hz 50Hz
Screw terminals With REVERSE device



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-REVERSE Series
Synthetical description	PLUG
Description	

The plug from the OPTIMA-REVERSE Series is designed for a rated voltage of 380-415V and a current of 16A. It features 3P+E poles and a 6h hour position, operating efficiently at both 50Hz and 60Hz frequencies. With a protection degree of IP44/IP54, it offers reliable performance in various environments. The plug is equipped with screw terminals and includes a REVERSE device for enhanced functionality. It is compatible with straight type outlets. The operating principle of the phase inverter is a notable feature, ensuring dependable performance for professional applications.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Options	With REVERSE device
Catalogue notes	Phase inverter
	Operating principle of the phase inverter

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000