218.125334

PLUG
125A 2P+E 3h >50-250V DC Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Description	

The OPTIMA Series plug, designed for high-performance electrical applications, operates at a rated voltage of >50-250V and a rated current of 125A, ensuring efficient power distribution. It features a 2P+E configuration with a 3h hour position, optimized for DC working frequency. The plug provides exceptional protection with an IP66/IP67/IP69 rating, offering robust defense against dust and water ingress. Equipped with mantle terminals, it facilitates secure and reliable connections. Available in a straight outlet type, this plug is engineered for demanding industrial environments. easy-plug.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	2P+E
Hour position	3h
Rated voltage	>50-250V
Working frequency	DC
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	GREY
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	EASY-PLUG