218.12534

PLUG
125A 3P+E 9h 200-250V 60Hz 50Hz
Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Description	

The OPTIMA Series plug, designed for high-performance electrical applications, operates at a rated voltage of 200-250V and a rated current of 125A, ensuring consistent power delivery. It features a 3P+E configuration with a 9h hour position, compatible with both 50Hz and 60Hz working frequencies. The plug provides exceptional protection with an IP66/IP67/IP69 rating, offering resistance against dust and water ingress. Equipped with mantle terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this plug is engineered for demanding industrial environments. easy-plug.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	3P+E
Hour position	9h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	EASY-PLUG