218.125371

PLUG
125A 3P+N+E 10h >50V 100-300Hz
Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG

Description

The OPTIMA Series plug, designed for high-performance electrical applications, operates with a rated current of 125A and accommodates a working frequency range of 100-300Hz. It supports a 3P+N+E configuration and is suitable for voltages exceeding 50V, with a 10h hour position. This plug offers exceptional protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Featuring mantle terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this plug is engineered for demanding industrial environments. easy-plug

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	3P+N+E
Hour position	10h
Rated voltage	>50V
Working frequency	100-300Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	EASY-PLUG