218.125372

PLUG
125A 3P+N+E 2h >50V >300-500Hz
Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Description	

The OPTIMA Series plug, engineered for high-performance electrical applications, is designed to operate at a rated voltage of over 50V and a rated current of 125A, ensuring robust power delivery. It features a 3P+N+E configuration with a 2h hour position, suitable for working frequencies between 300-500Hz. The plug offers exceptional protection with IP66/IP67/IP69 ratings, providing superior defense against dust and water ingress. Equipped with mantle terminals, it ensures secure and efficient connections. Available in a straight outlet type, this plug is a reliable choice for demanding industrial environments. easy-plug

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	3P+N+E
Hour position	2h
Rated voltage	>50V
Working frequency	>300-500Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	EASY-PLUG