# 218.1630P.TR

PLUG
16A 2P+E 4h 100-130V 60Hz 50Hz
Perforating terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | OPTIMA Series |
| Synthetical description | PLUG |
| Description | |

The OPTIMA Series plug, designed for robust electrical performance, operates at a rated voltage of 100-130V and a rated current of 16A, ensuring reliable power delivery. It features a 2P+E configuration with a 4h hour position, suitable for both 50Hz and 60Hz working frequencies. The plug offers superior protection with an IP66/IP67/IP69 rating, safeguarding against dust and water ingress. Equipped with perforating terminals, it ensures secure and efficient connections. Available in a straight outlet type, this plug includes a transparent handle, providing enhanced visibility and ease of use.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 16A |
| Poles | 2P+E |
| Hour position | 4h |
| Rated voltage | 100-130V |
| Working frequency | 60Hz |
| | 50Hz |
| Terminals | Perforating terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | YELLOW |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67/IP69 |
| Protection degree IK | IK08 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |
| Cable entry | CABLE GLAND |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

## OPTIONS & VARIOUS NOTES

| | |
|---|---|
| Notes | TRANSPARENT HANDLE |
| Catalogue notes | Transparent grip |



**SCAME PARRE S.p.A**
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000