218.1633P.TR

PLUG
16A 2P+E 6h 200-250V 60Hz 50Hz
Perforating terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Description	

The OPTIMA Series plug, designed for high-performance electrical applications, operates at a rated voltage of 200-250V and a rated current of 16A, ensuring consistent power delivery. it features a 2P+E configuration with a 6h hour position, compatible with both 50Hz and 60Hz working frequencies. The plug provides exceptional protection with an IP66/IP67/IP69 rating, effectively preventing dust and water ingress. Equipped with perforating terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this plug includes a transparent handle for enhanced visibility and ease of use, making it a reliable choice for demanding industrial settings.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Perforating terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	TRANSPARENT HANDLE
Catalogue notes	Transparent grip

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000