# 218.32333

PLUG
32A 2P+E 12h TST>50V 50Hz 60Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | OPTIMA Series |
| Synthetical description | PLUG |
| Description | |

The OPTIMA Series plug, engineered for robust electrical performance, is designed to operate at a rated current of 32A and a rated voltage greater than 50V, ensuring reliable power delivery. it features a 2P+E configuration with a 12h hour position, suitable for both 50Hz and 60Hz working frequencies. The plug offers superior protection with an IP66/IP67/IP69 rating, safeguarding against dust and water ingress. Equipped with screw terminals, it ensures secure and efficient connections. Available in a straight outlet type, this plug is a dependable choice for demanding industrial environments.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Poles | 2P+E |
| Hour position | 12h |
| Rated voltage | TST>50V |
| Working frequency | 50Hz |
| | 60Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | GREY |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67/IP69 |
| Protection degree IK | IK08 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |
| Cable entry | CABLE GLAND |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]