218.3236F.K

PLUG
32A 3P+E 6h 380-415V 50Hz 60Hz
Spring terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Description	

The OPTIMA Series plug, designed for high-performance electrical applications, operates at a rated voltage of 380-415V and a rated current of 32A. It features a 3P+E configuration with a 6h hour position, compatible with both 50Hz and 60Hz working frequencies. the plug offers superior protection with an IP66/IP67/IP69 rating, ensuring resistance against dust and water ingress. Equipped with spring terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this black-coloured plug is engineered for demanding industrial environments.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
	60Hz
Terminals	Spring terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	BLACK COLOURED
Catalogue notes	Black-coloured

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000