# 218.63365

PLUG
63A 3P+E 11h 440-460V 60Hz Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | OPTIMA Series |
| Synthetical description | PLUG |
| Description | |

The OPTIMA Series plug, designed for high-performance electrical applications, operates at a rated voltage of 440-460V and a rated current of 63A, ensuring consistent power delivery. It features a 3P+E configuration with an 11h hour position, optimized for a 60Hz working frequency. The plug provides exceptional protection with an IP66/IP67/IP69 rating, effectively guarding against dust and water ingress. Equipped with mantle terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this plug is engineered for demanding industrial environments. easy-plug functionality enhances usability, making it a reliable choice for professionals.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 63A |
| Poles | 3P+E |
| Hour position | 11h |
| Rated voltage | 440-460V |
| Working frequency | 60Hz |
| Terminals | Mantle terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | RED |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67/IP69 |
| Protection degree IK | IK08 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |
| Cable entry | CABLE GLAND |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

## OPTIONS & VARIOUS NOTES

| | |
|---|---|
| Notes | EASY-PLUG |



**SCAME PARRE S.p.A**
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000