235.3202

PLUG
32A 2P 10h 40-50V 20-25V DC Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	PLUG
Description	

The IEC309 Series plug, engineered for robust electrical performance, is designed to operate at a rated voltage of 20-25V and 40-50V with a rated current of 32A, ensuring reliable power delivery. it features a 2P configuration with a 10h hour position, suitable for DC working frequency. The plug offers superior protection with an IP66/IP67 rating, safeguarding against dust and water ingress. Equipped with screw terminals, it ensures secure and efficient connections. Available in a straight outlet type, this plug is a dependable choice for demanding industrial environments.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P
Hour position	10h
Rated voltage	40-50V
	20-25V
Working frequency	DC
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	WHITE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]