245.125933T

SURFACE MOUNT. APPLIANCE INLET
125A 2P+E 12h TST>50V 60Hz 50Hz
Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNT. APPLIANCE INLET
Description	

The OPTIMA-TOP Series surface mount appliance inlet is engineered for high-performance electrical applications. It features an angled outlet configuration with a 2P+E pole arrangement, supporting a rated current of 125A. Designed to operate efficiently at both 50Hz and 60Hz working frequencies, it accommodates a rated voltage greater than 50V. The inlet is equipped with a 12h hour position and offers superior protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Mantle terminals provide secure connections, and the product includes a cable gland, open threaded cable entry, and a threaded cap/cable sleeve for enhanced installation flexibility.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	2P+E
Hour position	12h
Rated voltage	TST>50V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	GREY
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	M63X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Cable gland included
	Open threaded cable entry
	Threaded cap/cable sleeve included