245.3295

SURFACE MOUNT. APPLIANCE INLET
32A 3P+N+E 9h 208-250V 50Hz 60Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-2 (2022)
EN IEC 60309-1 (2022)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	SURFACE MOUNT. APPLIANCE INLET
Description	

The OPTIMA Series surface mount appliance inlet is engineered for high-performance electrical applications. It features an angled outlet with a 3P+N+E configuration, supporting a rated current of 32A and a voltage range of 208-250V. Designed for both 50Hz and 60Hz working frequencies, it ensures versatile compatibility. The inlet provides exceptional protection with IP66/IP67/IP69 ratings, offering robust defense against dust and water ingress. Equipped with screw terminals, it guarantees secure and efficient connections. Additional features include a cable gland, open threaded cable entry, and threaded break-through knock out, enhancing its adaptability in demanding industrial environments.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	9h
Rated voltage	208-250V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	M32X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Cable gland included
	Open threaded cable entry
	Threaded break-through knock out