245.3296RV

SURFACE MOUNT. APPLIANCE INLET
32A 3P+E 6h 380-415V 50Hz 60Hz Screw terminals With REVERSE device



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-REVERSE Series
Synthetical description	SURFACE MOUNT. APPLIANCE INLET
Description	

The OPTIMA-REVERSE Series surface mount appliance inlet is engineered for high-performance electrical applications. Designed with an angled outlet, it features a 3P+E configuration, supporting a rated current of 32A and a rated voltage of 380-415V. This inlet operates efficiently at both 50Hz and 60Hz frequencies, with a 6h hour position. It offers exceptional protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Equipped with screw terminals, it includes a reverse device for enhanced functionality. The design incorporates a cable gland, open threaded cable entry, and threaded break-through knock out, providing versatile installation options for demanding industrial environments.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	M32X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Options	With REVERSE device
Catalogue notes	Cable gland included
	Open threaded cable entry
	Threaded break-through knock out