245.6395T

SURFACE MOUNT. APPLIANCE INLET
63A 3P+N+E 9h 208-250V 60Hz 50Hz
Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNT. APPLIANCE INLET
Description	

The OPTIMA-TOP Series surface mount appliance inlet is engineered for high-performance electrical applications. It features an angled outlet configuration with a 3P+N+E pole setup, supporting a rated current of 63A and a voltage range of 208-250V. Designed to operate efficiently at both 50Hz and 60Hz frequencies, it incorporates a 9h hour position. The inlet offers exceptional protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Equipped with mantle terminals, it guarantees secure connections. The product includes a cable gland, open threaded cable entry, and a threaded cap/cable sleeve, providing comprehensive installation solutions for industrial environments.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	9h
Rated voltage	208-250V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	M40X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Cable gland included
	Open threaded cable entry
	Threaded cap/cable sleeve included