247.16964

FLUSH MOUNTING APPLIANCE INLET
16A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz 60Hz 70X87MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The EUREKA Series flush mounting appliance inlet, engineered for precision and durability, is designed to support a rated voltage of 380V at 50Hz and 440V at 60Hz, with a rated current of 16A. Featuring a 3P+E configuration and a 3h hour position, it accommodates both 50Hz and 60Hz working frequencies. The inlet provides robust protection with an IP66/IP67 rating, effectively preventing dust and water ingress. It is equipped with screw terminals to ensure secure and efficient connections. Available in a 90° angled outlet type, this appliance inlet is crafted to meet the rigorous demands of industrial electrical environments.

Mounting version	FLUSH/SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+E
Hour position	3h
Rated voltage	380V 50Hz / 440V 60Hz
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH/SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	PG 16

DIMENSIONAL CHARACTERISTICS

Flange	70X87MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]