247.32934

FLUSH MOUNTING APPLIANCE INLET
32A 2P+E 3h >50-250V DC 70X87MM
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The EUREKA Series flush mounting appliance inlet, engineered for high-performance electrical applications, is designed with a 2P+E configuration and supports a rated current of 32A. It operates efficiently at a rated voltage range of >50-250V and is suitable for DC working frequencies. Featuring a 3h hour position, this inlet provides robust protection with an IP66/IP67 rating, ensuring resistance against dust and water ingress. Equipped with screw terminals, it guarantees secure and reliable connections. Available in a 90° angled outlet type, this appliance inlet is crafted to meet the rigorous demands of industrial environments.

Mounting version	FLUSH/SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P+E
Hour position	3h
Rated voltage	>50-250V
Working frequency	DC
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH/SURFACE MOUNTING
Colour	GREY
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	PG 16

DIMENSIONAL CHARACTERISTICS

Flange	70X87MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]