247.32964

FLUSH MOUNTING APPLIANCE INLET
32A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz 60Hz 70X87MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The EUREKA Series flush mounting appliance inlet, engineered for high-performance electrical applications, is designed with a 3P+E configuration to support a rated current of 32A. It operates efficiently at a rated voltage of 380V for 50Hz and 440V for 60Hz frequencies. Featuring a 3h hour position, this inlet ensures compatibility with various industrial setups. It offers robust protection with an IP66/IP67 rating, effectively guarding against dust and water ingress. The 90° angled outlet design, coupled with secure screw terminals, facilitates reliable and efficient connections, making it a dependable component for demanding industrial environments.

Mounting version	FLUSH/SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	3h
Rated voltage	380V 50Hz / 440V 60Hz
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH/SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	PG 16

DIMENSIONAL CHARACTERISTICS

Flange	70X87MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]