248.12598

FLUSH MOUNTING APPLIANCE INLET
125A 2P+E 9h 380-415V 60Hz 50Hz
114X114MM Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The OPTIMA Series flush mounting appliance inlet, engineered for high-performance electrical applications, operates at a rated voltage of 380-415V and a rated current of 125A. It features a 2P+E configuration with a 9h hour position, accommodating both 50Hz and 60Hz working frequencies. This inlet provides exceptional protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Equipped with mantle terminals, it guarantees secure and efficient connections. Available in a straight outlet type, this appliance inlet is designed to meet the rigorous demands of industrial environments.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	2P+E
Hour position	9h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated

DIMENSIONAL CHARACTERISTICS

Flange	114X114MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]