
# 248.16931

FLUSH MOUNTING APPLIANCE INLET
16A 2P+E 10h >50V 100-300Hz
75X75MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | OPTIMA Series |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET |
| Description | |

The OPTIMA Series flush mounting appliance inlet, engineered for robust electrical performance, is designed to accommodate a rated current of 16A and a rated voltage exceeding 50V. It features a 2P+E configuration with a 10h hour position, suitable for a wide working frequency range of 100-300Hz. The inlet offers superior protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Equipped with screw terminals, it guarantees secure and efficient connections. Available in a straight outlet type, this appliance inlet is a reliable choice for demanding industrial environments.

| | |
|---|---|
| Mounting version | FLUSH MOUNTING |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 16A |
| Poles | 2P+E |
| Hour position | 10h |
| Rated voltage | >50V |
| Working frequency | 100-300Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | FLUSH MOUNTING |
| Colour | GREEN |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67/IP69 |
| Protection degree IK | IK08 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |

## DIMENSIONAL CHARACTERISTICS

| | |
|---|---|
| Flange | 75X75MM |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]