
248.16965

FLUSH MOUNTING APPLIANCE INLET
16A 3P+E 11h 440-460V 60Hz
75X75MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The OPTIMA Series flush mounting appliance inlet, designed for high-performance electrical applications, operates at a rated voltage of 440-460V and a rated current of 16A. Featuring a 3P+E configuration with an 11h hour position, it is optimized for a 60Hz working frequency. This inlet provides exceptional protection with IP66/IP67/IP69 ratings, ensuring resilience against dust and water ingress. Equipped with screw terminals, it guarantees secure and efficient connections. Available in a straight outlet type, this appliance inlet is engineered to meet the rigorous demands of industrial environments.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+E
Hour position	11h
Rated voltage	440-460V
Working frequency	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated

DIMENSIONAL CHARACTERISTICS

Flange	75X75MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]