318.16475

CONNECTOR
16A 3P+N+E 11h 440-460V 60Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	CONNECTOR
Description	

The OPTIMA Series connector is engineered for demanding electrical industrial environments, offering a rated voltage of 440-460V and a rated current of 16A. This connector features a 3P+N+E configuration and an 11h hour position, ensuring reliable performance at a working frequency of 60Hz. With an IP66/IP67/IP69 protection degree, it provides exceptional resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a straight outlet type, it is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	11h
Rated voltage	440-460V
Working frequency	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]