326.1646

CONNECTOR
16A 3P+E 6h 380-415V 60Hz 50Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA Series
Synthetical description	CONNECTOR
Description	

The EUREKA Series connector is engineered for electrical industrial applications, offering a rated voltage of 380-415V and a rated current of 16A. This connector features a 3P+E configuration and a 6h hour position, ensuring reliable performance in demanding environments. With an IP66/IP67 protection degree, it provides superior resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a 90° angled outlet type, it is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]