335.16060

CONNECTOR
16A 2P 4h 20-25V 40-50V 100-200Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	CONNECTOR
Description	

The IEC309 Series connector is engineered for electrical industrial applications, offering a rated current of 16A and a working frequency of 100-200Hz. This connector features a 2P configuration and supports rated voltages of 20-25V and 40-50V. With a 4h hour position, it ensures reliable performance in demanding environments. The connector boasts an IP66/IP67 protection degree, providing excellent resistance to dust and water ingress. Equipped with screw terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this connector is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P
Hour position	4h
Rated voltage	20-25V
	40-50V
Working frequency	100-200Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]