335.16065

CONNECTOR
16A 2P 11h 20-25V 40-50V >400-500Hz Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	CONNECTOR
Description	

The IEC309 Series connector is designed for demanding electrical industrial environments, featuring a 2P configuration with a rated current of 16A. It operates at a working frequency of >400-500Hz and supports rated voltages of 20-25V and 40-50V. The connector is engineered with an 11h hour position and offers a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. Equipped with screw terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this connector is built to withstand the rigorous demands of industrial settings, ensuring both durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P
Hour position	11h
Rated voltage	20-25V
	40-50V
Working frequency	>400-500Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]