335.1607

CONNECTOR
16A 2P 10h 20-25V 40-50V DC Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	CONNECTOR
Description	

The IEC309 Series connector is designed for demanding electrical industrial environments, featuring a 2P configuration and supporting a rated current of 16A. It operates at a working frequency of DC and accommodates a rated voltage range of 20-25V to 40-50V. The connector is engineered with a 10h hour position and offers a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. Equipped with screw terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this connector is built to withstand rigorous industrial conditions, ensuring both durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P
Hour position	10h
Rated voltage	20-25V
	40-50V
Working frequency	DC
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	WHITE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]