# 335.1609

CONNECTOR
16A 3P 20-25V 60Hz 50Hz Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | IEC309 Series |
| Synthetical description | CONNECTOR |
| Description | |

The IEC309 Series connector is engineered for electrical industrial applications, offering a rated voltage of 20-25V and a rated current of 16A. This connector features a 3P configuration and supports working frequencies of 50Hz and 60Hz. With an IP66/IP67 protection degree, it provides exceptional resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a straight outlet type, it is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 16A |
| Poles | 3P |
| Rated voltage | 20-25V |
| Working frequency | 60Hz |
| | 50Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | VIOLET |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]