# 335.3206

CONNECTOR
32A 2P 12h 40-50V 60Hz 50Hz Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | IEC309 Series |
| Synthetical description | CONNECTOR |
| Description | |

The IEC309 Series connector is engineered for demanding electrical industrial environments, offering a rated voltage of 40-50V and a rated current of 32A. This connector features a 2P configuration and a 12h hour position, ensuring reliable performance across various applications. With an IP66/IP67 protection degree, it provides exceptional resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a straight outlet type, it is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Poles | 2P |
| Hour position | 12h |
| Rated voltage | 40-50V |
| Working frequency | 60Hz |
| | 50Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | WHITE |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]