# 335.32060

CONNECTOR
32A 2P 4h 20-25V 40-50V 100-200Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | IEC309 Series |
| Synthetical description | CONNECTOR |
| Description | |

The IEC309 Series connector is designed for demanding electrical industrial environments, featuring a rated current of 32A and a working frequency of 100-200Hz. This connector supports a rated voltage of 20-25V and 40-50V, with a 2P configuration and a 4h hour position. It offers a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. Equipped with screw terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this connector is engineered to meet the rigorous demands of industrial settings, ensuring durability and reliability.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Poles | 2P |
| Hour position | 4h |
| Rated voltage | 20-25V |
| | 40-50V |
| Working frequency | 100-200Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | GREEN |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]