335.32062

CONNECTOR
32A 2P 2h 20-25V 40-50V 300Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	CONNECTOR
Description	

The IEC309 Series connector is engineered for demanding electrical industrial environments, offering a rated current of 32A and a working frequency of 300Hz. This connector supports a voltage range of 20-25V and 40-50V, with a 2P configuration and a 2h hour position. It features an IP66/IP67 protection degree, ensuring exceptional resistance to dust and water ingress. Equipped with screw terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this connector is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P
Hour position	2h
Rated voltage	20-25V
	40-50V
Working frequency	300Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]