# 335.32064

CONNECTOR
32A 2P 3h 20-25V 40-50V 400Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | IEC309 Series |
| Synthetical description | CONNECTOR |
| Description | |

The IEC309 Series connector is engineered for demanding electrical industrial environments, offering a rated current of 32A and a working frequency of 400Hz. This connector features a 2P configuration and supports a rated voltage range of 20-25V and 40-50V. With a 3h hour position, it ensures reliable performance. The connector boasts an IP66/IP67 protection degree, providing excellent resistance to dust and water ingress. Equipped with screw terminals, it facilitates secure and efficient connections. Available in a straight outlet type, this connector is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

| | |
|---|---|
| Mounting version | PORTABLE |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Poles | 2P |
| Hour position | 3h |
| Rated voltage | 20-25V |
| | 40-50V |
| Working frequency | 400Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | PORTABLE |
| Colour | GREEN |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]