428.1663.MIL

FLUSH-MOUNTING SOCKET
16A 2P+E 6h 200-250V 50Hz 60Hz
75X75MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-MIL Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the OPTIMA-MIL Series, engineered for robust electrical performance, is designed to handle a rated voltage of 200-250V and a rated current of 16A, suitable for demanding industrial environments. It features a 2P+E configuration with a 6h hour position, ensuring reliable connectivity. The socket operates efficiently at both 50Hz and 60Hz frequencies. With a high protection degree of IP66/IP67/IP69, it offers superior resistance to dust and water ingress. The screw terminals provide secure and stable connections. Available in a straight outlet type, this green-coloured socket enhances visibility and installation flexibility.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DIMENSIONAL CHARACTERISTICS

Flange	75X75MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Green-coloured