428.3262

FLUSH-MOUNTING SOCKET
32A 3P+N+E 4h 100-130V 50Hz 60Hz
75X75MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the OPTIMA Series, engineered for robust electrical performance, is designed to handle a rated voltage of 100-130V and a rated current of 32A, making it suitable for demanding industrial environments. It features a 3P+N+E configuration with a 4h hour position, ensuring reliable connectivity. The socket operates efficiently at both 50Hz and 60Hz frequencies. With a high protection degree of IP66/IP67/IP69, it offers superior resistance to dust and water ingress. The screw terminals provide secure and stable connections, while the straight outlet design enhances accessibility and installation flexibility.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	4h
Rated voltage	100-130V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	YELLOW
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DIMENSIONAL CHARACTERISTICS

Flange	75X75MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]