428.63665

FLUSH-MOUNTING SOCKET
63A 3P+E 11h 440-460V 60Hz
100X110MM Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the OPTIMA Series, engineered for robust electrical performance, is designed to handle a rated voltage of 440-460V and a rated current of 63A, making it suitable for demanding industrial environments. It features a 3P+E configuration with an 11h hour position, ensuring reliable connectivity. The socket operates efficiently at a working frequency of 60Hz. With a high protection degree of IP66/IP67/IP69, it offers superior resistance to dust and water ingress. The mantle terminals provide secure and stable connections, while the straight outlet design enhances accessibility and installation flexibility.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+E
Hour position	11h
Rated voltage	440-460V
Working frequency	60Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DIMENSIONAL CHARACTERISTICS

Flange	100X110MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]