435.1615/R

FLUSH-MOUNTING SOCKET
16A 2P 20-25V 60Hz 50Hz 55X55MM
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the IEC309 Series, flush-mounting socket, is engineered for robust electrical performance. It is designed to handle a rated voltage of 20-25V and a rated current of 16A, making it suitable for demanding industrial environments. Featuring a 2P configuration, the socket operates efficiently at both 50Hz and 60Hz frequencies. With a high protection degree of IP66/IP67, it offers superior resistance to dust and water ingress. The screw terminals provide secure and stable connections, while the straight outlet design ensures straightforward installation and connectivity.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P
Rated voltage	20-25V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	VIOLET
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DIMENSIONAL CHARACTERISTICS

Flange	55X55MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]