435.3216/R

FLUSH-MOUNTING SOCKET
32A 2P 12h 40-50V 50Hz 60Hz
55X55MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the IEC309 Series, engineered for robust electrical performance, is designed to handle a rated voltage of 40-50V and a rated current of 32A, making it suitable for demanding industrial environments. it features a straight outlet configuration with a 2P design and a 12h hour position, ensuring reliable connectivity. The socket operates efficiently at both 50Hz and 60Hz frequencies. With a high protection degree of IP66/IP67, it offers superior resistance to dust and water ingress. The screw terminals provide secure and stable connections, enhancing installation reliability.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P
Hour position	12h
Rated voltage	40-50V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	WHITE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)

DIMENSIONAL CHARACTERISTICS

Flange	55X55MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000