435.32185

FLUSH-MOUNTING SOCKET
32A 3P 11h 40-50V 20-25V >400-500Hz 70X87MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the IEC309 Series, flush-mounting socket, is engineered for high-performance electrical applications. It is designed to accommodate a rated current of 32A and operates efficiently at frequencies exceeding 400-500Hz. The socket supports a rated voltage range of 20-25V and 40-50V, with a 3P configuration and an 11h hour position. It boasts a high protection degree of IP66/IP67, ensuring exceptional resistance to dust and water ingress. The angled outlet design facilitates ease of installation and accessibility, while the screw terminals provide secure and reliable connections, making it a robust choice for industrial environments.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P
Hour position	11h
Rated voltage	40-50V
	20-25V
Working frequency	>400-500Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	ANGLED
Contact material	CuZn (brass)

DIMENSIONAL CHARACTERISTICS

Flange	70X87MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]