# 457.3262

FLUSH-MOUNTING SOCKET
32A 3P+N+E 4h 100-130V 50Hz 60Hz
70X87MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Commercial Series | EUREKA Series |
| Synthetical description | FLUSH-MOUNTING SOCKET |
| Description | |

The flush-mounting socket from the EUREKA Series, flush-mounting socket, is engineered for robust electrical performance, accommodating a rated voltage of 100-130V and a rated current of 32A. It features a 3P+N+E configuration with a 4h hour position, ensuring reliable connectivity in industrial settings. The socket operates efficiently at both 50Hz and 60Hz frequencies. With a high protection degree of IP66/IP67, it offers superior resistance to dust and water ingress. The screw terminals provide secure and stable connections, while the 90° angled outlet design enhances accessibility and installation flexibility.

| | |
|---|---|
| Mounting version | FLUSH/SURFACE MOUNTING |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Poles | 3P+N+E |
| Hour position | 4h |
| Rated voltage | 100-130V |
| Working frequency | 50Hz |
| | 60Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | FLUSH/SURFACE MOUNTING |
| Colour | YELLOW |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67 |
| Protection degree IK | IK07 |
| Types of available outlets | 90° ANGLED |
| Contact material | CuZn (brass) |
| Cable entry | PG 16 |

## DIMENSIONAL CHARACTERISTICS

| | |
|---|---|
| Flange | 70X87MM |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]