457.32676

FLUSH-MOUNTING SOCKET
32A 3P+N+E 7h 480-500V 50Hz 60Hz
70X87MM Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA Series
Synthetical description	FLUSH-MOUNTING SOCKET
Description	

The flush-mounting socket from the EUREKA Series, flush-mounting socket, is engineered for high-performance in industrial settings, accommodating a rated voltage of 480-500V and a rated current of 32A. It features a 3P+N+E configuration with a 7h hour position, ensuring dependable connectivity. The socket is compatible with both 50Hz and 60Hz frequencies. With an IP66/IP67 protection degree, it offers exceptional resistance to dust and water ingress. The screw terminals ensure secure and stable connections, while the 90° angled outlet design enhances installation flexibility and accessibility.

Mounting version	FLUSH/SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	7h
Rated voltage	480-500V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH/SURFACE MOUNTING
Colour	BLACK
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Cable entry	PG 16

DIMENSIONAL CHARACTERISTICS

Flange	70X87MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]