518.1653TF

SURFACE MOUNTING SOCKET
16A 2P+E 6h 200-250V 50Hz 60Hz
Spring terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The OPTIMA-TOP Series surface mounting socket is designed for demanding industrial environments, featuring a rated voltage of 200-250V and a rated current of 16A. This 2P+E socket supports working frequencies of 50Hz and 60Hz and is equipped with a 6h hour position. It offers a high protection degree of IP66/IP67/IP69, ensuring excellent resistance to dust and water ingress. The socket includes spring terminals and angled outlets for efficient and fast wiring. Additionally, it features a threaded break-through knock out for secure installation. This product is engineered to meet the rigorous requirements of industrial applications.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
	60Hz
Terminals	Spring terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M20X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Notes	TOP - FAST WIRING
Catalogue notes	Threaded break-through knock out

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000