518.32565T

SURFACE MOUNTING SOCKET
32A 3P+E 11h 440-460V 60Hz Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The OPTIMA-TOP Series surface mounting socket is designed for demanding industrial environments, featuring a rated voltage of 440-460V and a rated current of 32A. This 3P+E socket is equipped with an 11h hour position and operates at a working frequency of 60Hz. It offers a high protection degree of IP66/IP67/IP69, ensuring exceptional resistance to dust and water ingress. The socket includes screw terminals and angled outlets for optimal connectivity. Additionally, it features a threaded break-through knock out for secure and flexible installation. This product is engineered to meet the rigorous standards required in industrial settings.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	11h
Rated voltage	440-460V
Working frequency	60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M32X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Threaded break-through knock out