518.63534T

SURFACE MOUNTING SOCKET 63A 2P+E 3h >50-250V DC Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The OPTIMA-TOP Series surface mounting socket is designed for demanding industrial environments, supporting a rated voltage of >50-250V and a rated current of 63A. This 2P+E socket operates at a 3h hour position with direct current (DC). It features a high protection degree of IP66/IP67/IP69, ensuring exceptional resistance to dust and water ingress. The socket is equipped with mantle terminals and angled outlets for optimal connectivity. It includes a cable gland, open threaded cable entry, and a threaded cap/cable sleeve for secure and efficient installation. This product is engineered to meet the rigorous standards of industrial applications.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	2P+E
Hour position	3h
Rated voltage	>50-250V
Working frequency	DC
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	GREY
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M40X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Cable gland included
	Threaded cap/cable sleeve included