518.63577T

SURFACE MOUNTING SOCKET
63A 3P+N+E 5h 600-690V 50Hz 60Hz
Mantle terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The OPTIMA-TOP Series surface mounting socket is designed for demanding industrial environments, featuring a rated voltage of 600-690V and a rated current of 63A. This 3P+N+E socket is equipped with a 5h hour position and supports working frequencies of 50Hz and 60Hz. It offers a high protection degree of IP66/IP67/IP69, ensuring excellent resistance to dust and water ingress. The socket includes mantle terminals and angled outlets for optimal connectivity. Additionally, it comes with a cable gland, open threaded cable entry, and a threaded cap/cable sleeve for secure installation. This product is engineered to meet rigorous industrial standards.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	5h
Rated voltage	600-690V
Working frequency	50Hz
	60Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLACK
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M40X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Cable gland included
	Threaded cap/cable sleeve included