
535.032114

SURFACE MOUNTING SOCKET
32A 2P 3h 40-50V 20-25V 400Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The IEC309 Series surface mounting socket is designed for demanding industrial environments, featuring a rated voltage of 20-25V and 40-50V with a rated current of 32A. This 2P socket operates at a working frequency of 400Hz and is equipped with a 3h hour position. It offers a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. The socket includes angled outlets and screw terminals for reliable connectivity. Additionally, it features an open threaded cable entry and a threaded cap/cable sleeve for secure installation. surface mounting socket

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P
Hour position	3h
Rated voltage	40-50V
	20-25V
Working frequency	400Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M25X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Threaded cap/cable sleeve included