535.16112

SURFACE MOUNTING SOCKET
16A 2P 2h 40-50V 20-25V 300Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The IEC309 Series surface mounting socket is designed for demanding industrial environments, featuring a rated voltage of 20-25V and 40-50V with a rated current of 16A. This 2P socket operates at a working frequency of 300Hz and is available in a straight outlet configuration. It offers a 2h hour position and a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. The socket is equipped with screw terminals for reliable connectivity. It includes a blank side with drilling point marks and a rubber cable sleeve for secure installation.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P
Hour position	2h
Rated voltage	40-50V
	20-25V
Working frequency	300Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Blank side with drilling point marks
	Rubber cable sleeve included