535.16134

SURFACE MOUNTING SOCKET
16A 3P 3h 40-50V 20-25V 400Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The IEC309 Series surface mounting socket is designed for demanding industrial environments, offering a rated voltage of 20-25V and 40-50V with a rated current of 16A. This 3P socket supports a working frequency of 400Hz and features a 3h hour position. It provides a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. The socket is equipped with screw terminals for reliable connectivity and includes a rubber cable sleeve for secure installation. Additionally, it features a blank side with drilling point marks, facilitating customization.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P
Hour position	3h
Rated voltage	40-50V
	20-25V
Working frequency	400Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	GREEN
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Blank side with drilling point marks
	Rubber cable sleeve included