535.3210

SURFACE MOUNTING SOCKET
32A 2P 20-25V 60Hz 50Hz Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

GENERAL CHARACTERISTICS

Commercial Series	IEC309 Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	

The IEC309 Series surface mounting socket is engineered for demanding industrial environments, offering a rated voltage of 20-25V and a rated current of 32A. This 2P socket supports working frequencies of 50Hz and 60Hz. It features a high protection degree of IP66/IP67, ensuring excellent resistance to dust and water ingress. The socket is equipped with screw terminals and straight outlets for reliable connectivity. Additionally, it includes a blank side with drilling point marks and a rubber cable sleeve for secure installation. This product is designed to meet the rigorous requirements of industrial applications.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P
Rated voltage	20-25V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	VIOLET
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Blank side with drilling point marks
	Rubber cable sleeve included