590.EM20005.SN

SWITCH DISCONNECTOR
200A 3P+SN IP65 460x520x245mm
K2 IK08 EMERGENCY YELLOW/RED
SN (WITH NEUTRAL LINK) GW 650°C



* Product image may be indicative

EN IEC 60947-3 (2021)
EN IEC 60947-1 (2021)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	ISOLATORS-TP Series
Synthetical description	SWITCH DISCONNECTOR
Description	

The switch disconnector isolators-tp series is engineered for emergency applications, featuring a durable construction with engineering plastic. With a handle of yellow/red for high visibility, this device is designed for surface mounting. It carries a rated current of 200A and operates efficiently at 200A in AC23A (415V). The switch disconnector offers a protection degree of IP65 and an impact resistance of IK08, ensuring reliability in demanding environments. Configured with 3P+SN poles and an unswitched neutral (solid neutral terminal block), it operates at a rated voltage of 690V. Notable features include blank sides, a door interlock, and a padlockable handle in the OFF position for up to three padlocks. The construction type is enclosed.

Type	EMERGENCY
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	200A
Poles	3P+SN
Switch size	K2
Rated voltage	690V
Rated insulation voltage (Ui)	1000VAC
Rated impulse voltage (Uimp)	12KV
Thermal current (Ithe)	250A
Current (Ie) AC21A (415V)	250A
Current (Ie) AC21A (500V)	250A
Current (Ie) AC21A (690V)	250A
Current (Ie) AC22A (415V)	200A
Current (Ie) AC22A (500V)	200A
Current (Ie) AC22A (690V)	200A
Current (Ie) AC23A (415V)	200A
Current (Ie) AC23A (500V)	160A
Current (Ie) AC23A (690V)	125A
Power AC23A (415V)	110kW
Short-time withstand current	8kA Icw(1s)
Conditional short circuit cur.	50kAeff
Associate fuse - type gG	200A

PHYSICAL CHARACTERISTICS

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	ENGINEERING PLASTIC
Protection degree IP	IP65
Installation temperature	-25°C/+60°C
Colour	YELLOW/RED
GLOW WIRE	GW 650°C
Protection degree IK	IK08
Padlock	ø8mm

DIMENSIONAL CHARACTERISTICS

Dimensions	460x520x245mm
Terminal bolt size	M8

Palm width	21mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Notes	SN (WITH NEUTRAL LINK)
Catalogue notes	Equipped with door interlock
	Blank sides
	Unswitched neutral (solid neutral terminal block)
	Handle padlockable in OFF position only (3 padlocks)