590.GE6305

SWITCH DISCONNECTOR
63A 4P(3P+N) IP66/IP69
160x220x115mm Y2 IK09 GENERAL
GREY/BLACK GW 650°C



* Product image may be indicative

EN IEC 60947-3 (2021)
EN IEC 60947-1 (2021)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

GENERAL CHARACTERISTICS

Commercial Series	ISOLATORS-TP Series
Synthetical description	SWITCH DISCONNECTOR
Description	

The switch disconnector isolators-tp series is engineered for industrial applications, featuring a durable construction of engineering plastic. With a handle of grey/black, this device is designed for high visibility and operational efficiency. It carries a rated current of 63A and operates at 63A in AC23A (415V), with a rated voltage of 690V. The switch disconnector is configured with 4P(3P+N) poles and a Y2 switch size, ensuring reliable performance. It offers a high protection degree of IP66/IP69 and an impact resistance of IK09, suitable for demanding environments. Notable features include a surface mounting version, a door interlock, a padlockable handle in both OFF (up to three padlocks) and ON (one padlock) positions, and a reversible base with late break and early make neutral pole.

Type	GENERAL
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	4P(3P+N)
Switch size	Y2
Rated voltage	690V
Rated insulation voltage (Ui)	690VAC
Rated impulse voltage (Uimp)	4kV
Thermal current (Ithe)	63A
Current (Ie) AC21A (415V)	63A
Current (Ie) AC21A (500V)	63A
Current (Ie) AC21A (690V)	63A
Current (Ie) AC22A (415V)	63A
Current (Ie) AC22A (500V)	63A
Current (Ie) AC22A (690V)	63A
Current (Ie) AC23A (415V)	63A
Current (Ie) AC23A (500V)	63A
Current (Ie) AC23A (690V)	38A
Current (Ie) AC3 (415V)	40A
Current (Ie) AC3 (690V)	25A
Power AC23A (415V)	30kW
Short-time withstand current	1,5kA Icw(1s)
Conditional short circuit cur.	10kAeff
Associate fuse - type gG	63A
Terminals - Rigid wires	10-35mm²

PHYSICAL CHARACTERISTICS

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	ENGINEERING PLASTIC
Protection degree IP	IP66/IP69
Installation temperature	-25°C/+60°C
Colour	GREY/BLACK
GLOW WIRE	GW 650°C
Protection degree IK	IK09
Padlock	ø8mm
Terminals tightening torque	3,6Nm

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000

DIMENSIONAL CHARACTERISTICS

Dimensions	160x220x115mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position
	Equipped with door interlock
	With late break and early make neutral pole
	Reversible base
	Blank side with drilling point marks on top side base
	Break-through cable entries on bottom side base