590.SGE4005

SWITCH DISCONNECTOR
40A 4P(3P+N) IP65 100x160x90mm
Y1 IK10 GENERAL GREY/BLACK



* Product image may be indicative

EN IEC 60947-3 (2021)
EN IEC 60947-1 (2021)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	ISOLATORS-INOX Series
Synthetical description	SWITCH DISCONNECTOR
Description	

The switch disconnector isolators-inox series is engineered for industrial applications, featuring a robust stainless steel [AISI304L] construction. With a handle of grey/black for professional aesthetics. This device carries a rated current of 40A and operates efficiently at 35A in AC23A (415V). It offers a high protection degree of IP65 and an impact resistance IK10, ensuring durability and resistance to demanding environments. The switch disconnector is configured with 4P(3P+N) poles and a late break and early make neutral pole, and a Y1 switch size, operating at a rated voltage of 690V. Notable features include a door interlock, a padlockable handle in both OFF (up to three padlocks) and ON (one padlock) positions, and a surface mounting version with blank sides.

Type	GENERAL
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	40A
Poles	4P(3P+N)
Switch size	Y1
Rated voltage	690V
Rated insulation voltage (Ui)	690VAC
Rated impulse voltage (Uimp)	4kV
Thermal current (Ithe)	40A
Current (Ie) AC21A (415V)	40A
Current (Ie) AC21A (500V)	32A
Current (Ie) AC21A (690V)	32A
Current (Ie) AC22A (415V)	40A
Current (Ie) AC22A (500V)	32A
Current (Ie) AC22A (690V)	32A
Current (Ie) AC23A (415V)	35A
Current (Ie) AC23A (500V)	25A
Current (Ie) AC23A (690V)	25A
Current (Ie) AC3 (415V)	28.5A
Current (Ie) AC3 (690V)	20A
Current (Ie) in DC22A (250V)	32A
Current (Ie) in DC22A (600V)	10A
Power AC23A (415V)	18.5kW
Short-time withstand current	400A Icw(1s)
Conditional short circuit cur.	10kAeff
Associate fuse - type gG	40A
Terminals - Flexible wires	1.5-10mm²
Terminals - Rigid wires	1.5-16mm²

PHYSICAL CHARACTERISTICS

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	STAINLESS STEEL [AISI304L]
Protection degree IP	IP65
Installation temperature	-25°C/+60°C
Colour	GREY/BLACK
Protection degree IK	IK10
Padlock	ø6mm

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000

Terminals tightening torque	0,8Nm

DIMENSIONAL CHARACTERISTICS

Dimensions	100x160x90mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	Blank sides
	Equipped with door interlock
	With late break and early make neutral pole
	Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position